

Reflective SILVER

BY MADICO

Reflective Silver 20

Reflective Silver 20 helps block solar energy and keeps you more comfortable in your home or office. The exterior reflectivity provides privacy and helps lower your energy costs.

Product Benefits

- Cuts Glare
- Increases Privacy
- Reduces Heat Gain
- Lowers Energy Costs
- Provides Shatter Resistance
- Rejects over 99% of UV Rays
- Slows Fading of Furnishings, Flooring

Why Madico?

Madico window films are an elegant, practical solution for comfort, protection and natural appearance. With over 100 years of innovation, Madico is a leading provider of advanced products engineered to meet your needs. When selecting the right window film for your home or building, you can trust in our professionally installed quality products.

About Madico

Headquartered in Tampa Bay, Florida, Madico, Inc. innovates, manufactures, and distributes a broad range of protective, functional and decorative materials-based solutions including films, coatings and laminates for various industries worldwide from automotive and architecture to healthcare and aerospace. Since 1903, Madico has pioneered industry-first products with an unrivaled commitment to quality and dedication to its customers. Madico is a fully-owned subsidiary of Lintec USA Holdings, Inc. For more information, visit www.madico.com.



U.S. 888.887.2022 • Intl. +1 727.327.2544
contact@madico.com • madico.com

MADICO[®]

The Clear Choice for Architectural Film



Reflective Silver 20

Performance Measurements

- Visible Light:
- Transmitted..... 19%
 - Reflected Exterior..... 55%
 - Reflected Interior..... 56%
 - Glare Reduction..... 79%
- Total Solar Energy:
- Transmitted..... 13%
 - Reflected 45%
 - Absorbed..... 42%
- Shading Coefficient..... 0.28
 - Solar Heat Gain Coefficient..... 0.24
 - U Factor..... 0.88
 - Ultraviolet Rejection Exceeds 99%
 - Emissivity..... 0.58
 - Light to Solar Gain..... 0.78
 - Total Solar Energy Rejection..... 76%
 - Infrared Rejection*..... 94%
 - Infrared Energy Rejection 78%

* Near IR range (780-2500nm)
 Performance measurement definitions can be found at www.madico.com

Read in accordance with National Fenestration Rating Council (NFRC) standards on 6mm clear glass.

Reflective Silver 20 Performance on Installed Windows as Certified by the National Fenestration Rating Council (NFRC)

Type	Default Glazing Reference	SHGC without Film	SHGC With Film	VLT Without Film	VLT With Film	U Factor
Residential	3 mm (1/8in.) clear	0.72	0.19	0.74	0.15	0.97
Residential†	3 mm (1/8in.) clear 3 mm (1/8in.) clear	0.64	0.25	0.67	0.15	0.67
Non Residential	6 mm (1/4in.) clear	0.73	0.22	0.78	0.16	0.90
Non Residential	6 mm (1/4in.) grey	0.52	0.26	0.39	0.08	0.90
Non Residential†	6 mm (1/4in.) clear 6 mm (1/4in.) clear	0.63	0.31	0.69	0.15	0.55
Non Residential†	6 mm (1/4in.) grey 6 mm (1/4in.) clear	0.41	0.24	0.35	0.07	0.55

† Dual pane window

Specification Use Statement

Reported values are typical properties and should not be used as a specification. Since the user is aware of the specific conditions in which the product is to be used, it is the user's responsibility to determine whether the product is suitable for intended use. If you need verification regarding specific use or additional information, please contact Madico Window Films or your local Madico Authorized Dealer. Since there can be variations in published data between printed materials, please visit www.madico.com for the latest reported performance measurements.